



Quotation




To	Deliver to	
Thermoproof Surplus	Pick up Cobble Hill	
Quote No.	Customer Ref.	Quote Date
002060	Nail-on	2025-02-06




All Quoted Prices are Good for 15 Days

Sales Line	Details	Qty	Rate	Amount
0001  <p style="font-size: small; color: blue;">Viewed from Outside</p>	Pacific 6000 Series Picture O 24 3/16w x 37 5/16h 3 Low-E270-1/2-3 Clear(3/4) Dimension Type Frame Size Colour White Slider Frame 6640 Nail-On Installation Type Supply Only Weight: 26.99 lbs	2	147.66	295.32
Thermal Data & NAFS:				
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #
1.47	0.32	26	0.53	N/A
Performance Grade	Design Pressure	Water Penetration	Air Tightness	
R - PG30	1920	720	Fixed	
0002  <p style="font-size: small; color: blue;">Viewed from Outside</p>	Pacific 6000 Series Picture O 25 3/4w x 48 1/4h 3 Low-E270-1/2-3 Clear(3/4) Dimension Type Frame Size Colour White Slider Frame 6640 Nail-On Installation Type Supply Only Weight: 36.18 lbs	1	176.27	176.27
Thermal Data & NAFS:				
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #
1.47	0.32	26	0.53	N/A
Performance Grade	Design Pressure	Water Penetration	Air Tightness	
R - PG30	1920	720	Fixed	

C/FWD \$

471.59

Quote No.	Customer Ref.		Quote Date																							
002060	Nail-on		2025-02-06																							
Sales Line	Details			Qty	Rate	Amount																				
0003	 <p>Pacific 6000 Series Picture O 21 0/0w x 38 1/8h 3 Low-E270-1/2-3 Clear(3/4) Dimension Type Frame Size Colour White Slider Frame 6640 Nail-On Installation Type Supply Only Weight: 24.31 lbs</p> <p>Viewed from Outside</p> <p>Thermal Data & NAFS:</p> <table border="1"> <thead> <tr> <th>U-Factor</th> <th>Solar Heat Gain</th> <th>Energy Rating</th> <th>Visible Trans.</th> <th>NRCan #</th> </tr> </thead> <tbody> <tr> <td>1.47</td> <td>0.32</td> <td>26</td> <td>0.53</td> <td>N/A</td> </tr> <tr> <th>Performance Grade</th> <th>Design Pressure</th> <th>Water Penetration</th> <th>Air Tightness</th> <td></td> </tr> <tr> <td>R - PG30</td> <td>1920</td> <td>720</td> <td>Fixed</td> <td></td> </tr> </tbody> </table>			U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #	1.47	0.32	26	0.53	N/A	Performance Grade	Design Pressure	Water Penetration	Air Tightness		R - PG30	1920	720	Fixed		1	141.25	141.25
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #																						
1.47	0.32	26	0.53	N/A																						
Performance Grade	Design Pressure	Water Penetration	Air Tightness																							
R - PG30	1920	720	Fixed																							
0004	 <p>Pacific 6000 Series Picture O 29 1/16w x 45 3/8h 3 Low-E270-1/2-3 Clear(3/4) Dimension Type Frame Size Colour White Slider Frame 6640 Nail-On Installation Type Supply Only Weight: 38.10 lbs</p> <p>Viewed from Outside</p> <p>Thermal Data & NAFS:</p> <table border="1"> <thead> <tr> <th>U-Factor</th> <th>Solar Heat Gain</th> <th>Energy Rating</th> <th>Visible Trans.</th> <th>NRCan #</th> </tr> </thead> <tbody> <tr> <td>1.47</td> <td>0.32</td> <td>26</td> <td>0.53</td> <td>N/A</td> </tr> <tr> <th>Performance Grade</th> <th>Design Pressure</th> <th>Water Penetration</th> <th>Air Tightness</th> <td></td> </tr> <tr> <td>R - PG30</td> <td>1920</td> <td>720</td> <td>Fixed</td> <td></td> </tr> </tbody> </table>			U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #	1.47	0.32	26	0.53	N/A	Performance Grade	Design Pressure	Water Penetration	Air Tightness		R - PG30	1920	720	Fixed		1	184.55	184.55
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #																						
1.47	0.32	26	0.53	N/A																						
Performance Grade	Design Pressure	Water Penetration	Air Tightness																							
R - PG30	1920	720	Fixed																							
0005	 <p>OG:09791 w-2 Summit 7000 Series Casement R 19 1/2w x 45 1/2h 3 Low-E270-1/2-3 Clear(3/4) Dimension Type Frame Size Colour White Window Frame 6433 Nail-On Screen Lip Screen Mesh Fiberglass Handle Evolution Handle Colour West Coast White Installation Type Supply Only Weight: 37.83 lbs</p> <p>Viewed from Outside</p> <p>Thermal Data & NAFS:</p> <table border="1"> <thead> <tr> <th>U-Factor</th> <th>Solar Heat Gain</th> <th>Energy Rating</th> <th>Visible Trans.</th> <th>NRCan #</th> </tr> </thead> <tbody> <tr> <td>1.51</td> <td>0.24</td> <td>21</td> <td>0.46</td> <td>N/A</td> </tr> <tr> <th>Performance Grade</th> <th>Design Pressure</th> <th>Water Penetration</th> <th>Air Tightness</th> <td></td> </tr> <tr> <td>LC - PG40</td> <td>2160</td> <td>720</td> <td>A3</td> <td></td> </tr> </tbody> </table>			U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #	1.51	0.24	21	0.46	N/A	Performance Grade	Design Pressure	Water Penetration	Air Tightness		LC - PG40	2160	720	A3		1	355.91	355.91
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #																						
1.51	0.24	21	0.46	N/A																						
Performance Grade	Design Pressure	Water Penetration	Air Tightness																							
LC - PG40	2160	720	A3																							

Quote No.	Customer Ref.	Quote Date																						
002060	Nail-on	2025-02-06																						
Sales Line	Details	Qty	Rate	Amount																				
0006	 <p>Summit 7000 Series Picture O 41 9/16w x 48 0/0h 3 Low-E270-1/2-3 Clear(3/4) 7/8" SDL Dimension Type Frame Size Colour White Fixed Frame 6433 Nail-On Grid Side External Installation Type Supply Only Weight: 53.98 lbs</p> <p>Viewed from Outside</p> <p>Thermal Data & NAFS:</p> <table border="1"> <thead> <tr> <th>U-Factor</th> <th>Solar Heat Gain</th> <th>Energy Rating</th> <th>Visible Trans.</th> <th>NRCan #</th> </tr> </thead> <tbody> <tr> <td>1.52</td> <td>0.31</td> <td>25</td> <td>0.59</td> <td>N/A</td> </tr> <tr> <th>Performance Grade</th> <th>Design Pressure</th> <th>Water Penetration</th> <th>Air Tightness</th> <td></td> </tr> <tr> <td>LC - PG40</td> <td>2640</td> <td>720</td> <td>Fixed</td> <td></td> </tr> </tbody> </table>	U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #	1.52	0.31	25	0.59	N/A	Performance Grade	Design Pressure	Water Penetration	Air Tightness		LC - PG40	2640	720	Fixed		1	250.00	250.00
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #																				
1.52	0.31	25	0.59	N/A																				
Performance Grade	Design Pressure	Water Penetration	Air Tightness																					
LC - PG40	2640	720	Fixed																					
0007	 <p>Pacific 6000 Series Picture O 24 1/8w x 37 0/0h 3 Low-E270-1/2-3 Clear(3/4) Dimension Type Frame Size Colour White Slider Frame 6640 Nail-On Installation Type Supply Only Weight: 26.73 lbs</p> <p>Viewed from Outside</p> <p>Thermal Data & NAFS:</p> <table border="1"> <thead> <tr> <th>U-Factor</th> <th>Solar Heat Gain</th> <th>Energy Rating</th> <th>Visible Trans.</th> <th>NRCan #</th> </tr> </thead> <tbody> <tr> <td>1.47</td> <td>0.32</td> <td>26</td> <td>0.53</td> <td>N/A</td> </tr> <tr> <th>Performance Grade</th> <th>Design Pressure</th> <th>Water Penetration</th> <th>Air Tightness</th> <td></td> </tr> <tr> <td>R - PG30</td> <td>1920</td> <td>720</td> <td>Fixed</td> <td></td> </tr> </tbody> </table>	U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #	1.47	0.32	26	0.53	N/A	Performance Grade	Design Pressure	Water Penetration	Air Tightness		R - PG30	1920	720	Fixed		1	147.41	147.41
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #																				
1.47	0.32	26	0.53	N/A																				
Performance Grade	Design Pressure	Water Penetration	Air Tightness																					
R - PG30	1920	720	Fixed																					
0008	 <p>12009 Window 5 Pacific 6000 Series Horizontal Slider XO 34 1/4w x 20 1/4h 3 LE270-7/16-3 LE180-7/16-4 Rain(1 5/16) Dimension Type Frame Size Colour White Slider Frame 6626 Nail-On Screen Flat Screen Mesh Fiberglass Installation Type Supply Only Weight: 33.16 lbs</p> <p>Viewed from Outside</p> <p>Thermal Data & NAFS:</p> <table border="1"> <thead> <tr> <th>U-Factor</th> <th>Solar Heat Gain</th> <th>Energy Rating</th> <th>Visible Trans.</th> <th>NRCan #</th> </tr> </thead> <tbody> <tr> <td>0.93</td> <td>0.26</td> <td>34</td> <td>0.48</td> <td>NR6010-36558418-ES5</td> </tr> <tr> <th>Performance Grade</th> <th>Design Pressure</th> <th>Water Penetration</th> <th>Air Tightness</th> <td></td> </tr> <tr> <td>R - PG30</td> <td>2160</td> <td>330</td> <td>A3</td> <td></td> </tr> </tbody> </table>	U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #	0.93	0.26	34	0.48	NR6010-36558418-ES5	Performance Grade	Design Pressure	Water Penetration	Air Tightness		R - PG30	2160	330	A3		1	433.43	433.43
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #																				
0.93	0.26	34	0.48	NR6010-36558418-ES5																				
Performance Grade	Design Pressure	Water Penetration	Air Tightness																					
R - PG30	2160	330	A3																					

Quote No.	Customer Ref.		Quote Date			
002060	Nail-on		2025-02-06			
Sales Line	Details		Qty	Rate	Amount	
0009	HOLD	10369-3	1	500.00	500.00	
 <p>Viewed from Outside</p>		Pacific 6000 Series Horizontal Slider XO 46 1/2w x 46 1/2h 3 LE270-1/2-3 Clear-1/2-3 LE180(1 3/8)				
		Dimension Type				Frame Size
		Colour				White
		Slider Frame				6626 Nail-On
		Screen				Flat
		Screen Mesh				Fiberglass
		Installation Type				Supply Only
		Weight: 94.52 lbs				
Thermal Data & NAFS:						
U-Factor	Solar Heat Gain	Energy Rating	Visible Trans.	NRCan #		
0.93	0.26	34	0.48	NR6010-36558418-ES5		
Performance Grade	Design Pressure	Water Penetration	Air Tightness			
R - PG30	2160	330	A3			

Payment Terms

50% Deposit, Remainder Due at Delivery

Total		\$ 2,484.14
PST	7.00 %	\$ 173.89
GST	5.00 %	\$ 124.21
Grand Total		\$ 2,782.24

Thermoproof Windows and Doors

We are the largest locally owned window and door manufacturer on the island. We started out with wood windows, transitioned to aluminum and have now perfected our products using vinyl. Our components may have changed over the years, but our focus on exceptional quality and customer service remains steadfast.